

Desiccant Regenerative Air Dryer Systems

Reading Technologies, Inc. is pleased to offer this innovative product to its already extensive line. The Desiccant Regenerative Air Dryers provide the DRY-EST, cost-efficient air required for your critical applications with low maintenance and utility requirements. Just another way RTi is transforming the compressed air industry.



Exsiccator Series
DRAD 15, 8, 4 (shown)

Features & benefits

- The driest air you need
-40°F dew point at rated flow
- Simple, efficient design...
only two moving parts!
- Low maintenance “plug
& play” design
- The dry-cost advantage
uses <0.1 Amps of 110vac
no heat required
- Tower sequencing indicator
lights
- Quiet operation
- Easy wall mount design
- Non-corrosive aluminum towers
- NEMA 4 enclosure

Applications

CNC Machine Tools, Outdoor HVAC Controls, Food Process Equipment, Graphic Printers, Robotic Machinery, Lab & Instrument Air, Critical Valve Applications, Electronic Test Equipment, Laser & Plasma Cutters, Air Knife & Blanketing Applications, Dust Collectors, Purge & Back Fill Applications



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe



Desiccant Regenerative Air Dryer Systems

DRAD-4

- Inlet: 3/8" NPT
- Outlet: 1/4" NPT
- Inlet Flow scfm (max): 4.8 at 100 PSI
- Outlet Flow scfm (max): 3.6 at 100 PSI
- -40°F Dew Point at rated flow
- Max Temp: 120°F
- Max Pressure: 100 PSI
- 110 VAC with 5' power cord



DRAD-8

- Inlet: 3/8" NPT
- Outlet: 1/4" NPT
- Inlet Flow scfm (max): 9.2 at 100 PSI
- Outlet Flow scfm (max): 8.0 at 100 PSI
- -40°F Dew Point at rated flow
- Max Temp: 120°F
- Max Pressure: 100 PSI
- 110 VAC with 5' power cord



DRAD-15

- Inlet: 3/8" NPT
- Outlet: 3/8" NPT
- Inlet Flow scfm (max): 18 at 100 PSI
- Outlet Flow scfm (max): 15 at 100 PSI
- -40°F Dew Point at rated flow
- Max Temp: 120°F
- Max Pressure: 100 PSI
- 110 VAC with 5' power cord



DRAD-25

- Inlet: 3/8" NPT
- Outlet: 3/8" NPT
- Inlet Flow scfm (max): 29.5 at 100 PSI
- Outlet Flow scfm (max): 25 at 100 PSI
- -40°F Dew Point at rated flow
- Max Temp: 120°F
- Max Pressure: 100 PSI
- 110 VAC with 5' power cord

